



** : QUOTA MINIMA PER INSERIMENTO CARTUCCIA
 ** : MINIMUM DISTANCE FOR CARTRIDGE HANDLING
 * : LA QUOTA PUO' VARIARE DA 0-17 mm GRAZIE AI PIEDI REGOLABILI
 * : THE RATE CAN VARY FROM 0-17 mm THANKS TO ADJUSTABLE FEET

POS.	CODE	DENOMINATION			QUANTIT	MATERIALS
ALL DIMENSIONS MILLIMETERS	ALL SURFACES FINISH ROUGHNESS IN Ra μm	GENERAL TOLLERANCES UNLESS OTHERWISE SPECIFIED UNI-EN 22768-mk UNI-EN 22768-c			NOT QUOTED FILLET R=0.3 CHAMFER 0.3x45°	
SIMILAR TO	CRITICAL INDEX	WORK ORDER	JOB	QUANTITY	DRAWN DATE 26/06/2015 BY Tecnico	APPROVED DATE BY
DENOMINATION FILTERBLACK FBKA-01 1x20"					CODE FBKA316LBL0120M	REV.
Everblue				MODIFICATION	DATE	BY
REPRODUCTION IS PROHIBITED - ALL RIGHTS RESERVED ACCORDING TO THE LAW				BARCODE	SCALE 1:5	PROJECTION