

## Housings for filter cartridges

### STAINLESS STEEL SS 316 L HOUSINGS

### FM0-BHF

[Link to product's PDF drawing](#)


#### TECHNICAL FEATURES:

Type	FM0-BHF
Material	AISI 316 L
In/Out	1" 1/2 BSP M

#### DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50 C°

#### CARTRIDGES

N° cartridges	1
Type end caps	BIG BHF
Inner diameter min	36 mm
Outer diameter	115 mm
Cartridges height	9" 3/4,20"



#### APPLICATIONS

Water

Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	Capacity empty 2 bar (l/min)	End cap	Quantity box	€/each
FM0316LBHF0109M	FM0-BHF 1x9" 3/4	Ceramic blasted	9" 3/4	1" 1/2 BSP M	166	BHF	1	-
FM0316LBHF0120M	FM0-BHF 1x20"	Ceramic blasted	20"	1" 1/2 BSP M	166	BHF	1	-

# Housings for filter cartridges

## STAINLESS STEEL SS 316 L HOUSINGS

### FM0-BHF

#### HOUSINGS CODE LIST

Model	Material	Cartridges end cap typ	Cartridges n°	Cartridges height	Specs and finishing
FM0	AISI 316 L 316L	BIG BHF BHF	1 01	9" 3/4 20" 09 20	Ceramic blasted M



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



#### European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.  
 PED REFERENCES: PED 2014/68/EU  
 FLUID: NOT DANGEROUS  
 ARTICLES: 4.1 LETTER (a) (ii)  
 4.3  
 13.1