





## Bag filter housing

# **STAINLESS STEEL SS 316 BAG FILTER HOUSINGS**

# **FILTRO FBE-2RS**



#### **FEATURES**

Model	FILTRO FBE-2RS	
Material	SS 316	
In/Out	32" DN100 FLANGE EN1092	

#### **DESIGN DATA**

Max working pressure	10 bar
Hydraulic test pressure	12 bar

Max working temperature	80°C
Life test	100.000 cycles from 0 to 8 bar

#### **BAGS**

07 Diam. 7" (175/180 mm)
32" (810 mm)
161 mm / 166 mm
180 mm
3





#### **RING TYPE**

SI7 Internal ring	175/180 mm
SW7 Welded ring	175/180 mm

#### **APPLICATIONS**

Water

Code	Description	Specs, colors and particular finishing	In/Out	Bag's end cap	Quantity box	-
FBE2RS316070232M	FILTRO FBE-2RS 2x32"	Ceramic blasted	32" DN100 FLANGE EN1092	07	1	







### Bag filter housing

### STAINLESS STEEL SS 316 BAG FILTER HOUSINGS

# **FILTRO FBE-2RS**

#### **HOUSINGS CODE LIST** Model Material Ring diameter N° bags Bags height Specs and finishing 32" (810 mm) AISI 316 316 07 Diam. 7" 02 32 Ceramic blasted FBE2RS 07 (175/180 mm)



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



#### **European Community members only.**

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014.

These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS ARTICLES: 4.1 LETTER (a) (ii)

Design code: EN 13445 - 3