

## PROBLUE RO Reverse osmosis membrane + housing

# PROBLUE RO TW4040 105 XLE HF

[Link to product's PDF drawing](http://www.everblue.it/CadDrawings/PROBLUE RO TW4040105 XLE HF_1.pdf)

[http://www.everblue.it/CadDrawings/PROBLUE RO TW4040105 XLE HF\\_1.pdf](http://www.everblue.it/CadDrawings/PROBLUE RO TW4040105 XLE HF_1.pdf)

### FEATURES

Model	PROBLUE RO
Configuration	Spiral wound membrane
Membrane material	Polyamide composite
Housing material	PVC
Membrane area	105 ft <sup>2</sup>
Weight	16,8 lbs (3,6 Kg)

### TECHNICAL SPECS

Flow min.	3700 gpd (14,0 m3/d)
Rejection	98,8% nominale 98,0% (minimo)

### TEST CONDITIONS

Solution NaCl	1500 ppm
Pressure	150 psi (10,3 bar)
Temperature	77°F (25°C)
Permeate recovery	15%
PH Range	6,5 - 7,0

### MAX OPERATING LIMITS

Operating pressure	150 psi (10 bar)
Pressure drop	10 psi (0,7 bar)
Temperature	113°F (45°C)
Feed flow	16 gpm (3,6 m3/h)
Clorine concentration	< 0,1 ppm
Feed water SDI max (15 min.)	5,0
Feed water turbidity max	1,0 NTU
Feed water pH	3,0 - 10,0
Min. ration of concentrate to permeate flow each elem.	5:1

Code	Description	Quantity box	-
PBROTW4040105XLEHF	PROBLUE RO TW4040 105 XLE HF	1	

# PROBLUE RO Reverse osmosis membrane + housing

## PROBLUE RO TW4040 105 XLE HF

### MEMBRANES CODE LIST

Model		Type	Diameter		Length		Area		Pressure		Spec/rejection	
PBRO		TW	4"	40	40"	40	105 ft <sup>2</sup>	105	Extra Low Energy	XLE	High Flux	HF

*Approximate picture. Configuration and measures choice will lead to the assembly of a product which could differ from those shown in figure*



*The permeate flow for individual elements may vary + or - of 15%. The elements are vacuum sealed in a polyethylene bag and containing less than 1.0% sodium metabisulphite and 10% propylene glycol solution.*

The limitations mentioned in the "Operating Limits" are for general use. For specific projects, the values may be more conservative to ensure the best performance and a longer life of the membrane.

The customer is fully responsible for the effects on the elements of incompatible chemicals. The presence of free chlorine and other oxidizing agents will cause damage to the membrane. The damage is not covered under warranty.

Everblue believes the information and data contained in this document are accurate and useful. The information and data are provided in good faith, but without guarantee, as conditions and methods of use of our products are out of our control.

Everblue is in no way responsible for the results obtained or damages caused by the application of information and data provided.

It is the user's responsibility to determine the appropriateness of Everblue's products for the user's specific ed uses.

Everblue doesn't provide any performance warranty, all the implied warranties of merchantability or fitness for a particular purpose are expressly excluded.

Please consult the manufacturer for detailed warranty information.

We reserve the right to modify or amend the specifications without prior notice.