Housings for filter cartridges

FIBERGLASS HOUSINGS

FILTERBLUE FBL-03-2RS

DOWNLOAD TECHNICAL DRAWING PDF

DOWNLOAD EXPLODED VIEW PDF

TECHNICAL FEATURES

Type	FILTERBLUE FBL-03-2RS
Material	FRP (Fiberglass)
In/Out	DN 125 FLANGE DN8063 PN16

MATERIAL

Body	FRP
End plug	PVC
In-Out	POM
Drain/Vent	POM

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50 C°

SCOPE OF USE

Water
Sea water

CARTRIDGES

N° cartrigdes	6
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartidges height	20"

Code	Description	Specs, colors and particular finishing	Cartidges	In/Out	End cap	Euro/each
FBL2RSFRPBL0620WH	FILTERBLUE FBL-03-2RS 6x20"	White	20"	DN 125 FLANGE DN8063 PN16	BL	Login

For determining the flow rate, we recommend using the calculation software Everblue Selector or consulting our virtual assistant BlueBot available on the homepage.

Housings for filter cartridges

FIBERGLASS HOUSINGS

FILTERBLUE FBL-03-2RS

HOUSINGS CODE LIST

Model	Material		Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
FBL2RS	FRP (Fiberglass)	FRP	BL	BL	6	06	20"	20	White	WH

Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014.
These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.
PED REFERENCES: PED 2014/68/EU
FLUID: NOT DANGEROUS
ARTICLES: 4.1 LETTER (a) (ii)
4.3
13.1
Design code: BS EN 13923 2005