

Housings for filter cartridges

POLYPROPYLENE HOUSINGS

FILTERBIG FBG



[DOWNLOAD TECHNICAL DRAWING PDF](#)



[DOWNLOAD EXPLODED VIEW PDF](#)

TECHNICAL FEATURES

Type	FILTERBIG FBG
Material	PP (Polypropylene)
In/Out	1" 1/2 BSP F

DESIGN DATA

Max working pressure	8 bar
Hydraulic test pressure	12 bar
Burst pressure	25 bar
Max working temperature	50 C°

SCOPE OF USE

Water
Sea water

CARTRIDGES



N° cartridges	1
Type end caps	FilterBig
Inner diameter min	36 mm
Outer diameter	120 mm
Cartridges height	20", 9" 3/4



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
FBGPPBHF0109WH	FILTERBIG FBG 1x9" 3/4	White	9" 3/4	1" 1/2 BSP F	BHF	Login
FBGPPBHF0120WH	FILTERBIG FBG 1x20"	White	20"	1" 1/2 BSP F	BHF	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).


ACCESSORIES

Code	Description	Opzional	?/each	Pic
A6010090	Polypropylene wrench	Yes	Login	
PN020100	Metal single bracket BIG	Yes	Login	

Housings for filter cartridges

POLYPROPYLENE HOUSINGS

FILTERBIG FBG

PN020040	Metal double bracket BIG	Yes	Login	
----------	--------------------------	-----	-------	---

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FBG	PP (Polypropylene) PP	FilterBig BHF	1 01	9" 3/4 20" 09 20	White WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the PED 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and desing that respect the conditions established by the directive above mentioned.

PED: REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13.1