





PARMA - ITALY https://www.everblue.it

Housings for filter cartridges

FILTERBLUE MAXI-BL-12

Link to product's PDF drawing



TECHNICAL FEATURES:

Туре	FILTERBLUE MAXI-BL-12
Material	FRP (Fiberglass)
In/Out	DN 200 FLANGE EN1092

MATERIAL

Body	FRP
Heads	FRP
In/Out	FRP
Drain/Vent	FRP

DESIGN DATA

Max working pressure	6 bar	
Hydraulic test pressure	7.8 bar	
Max working temperature	50 C°	

CARTRIDGES

N° cartrigdes	12
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartidges height	20"





APPLICATIONS

Water	
Sea water	

Code	Description	Specs, colors and particular finishing	Cartidge s	In/Out	Capacity empty 2 bar (I/min)	End cap	Quantity box	€/each
FBLMFRPBL1220WH	FILTERBLUE MAXI-BL-12 12x20"	White	20"	DN 200 FLANGE FN1092	3.600	BL	1	-







PARMA - ITALY https://www.everblue.it

Housings for filter cartridges FIBERGLASS HOUSINGS

FILTERBLUE MAXI-BL-12

HOUSINGS CODE LIST

Model	Material C	artridges end cap typ		Cartridges n°		Cartridges height		Specs and finishing	
FBLM	FRP (Fiberglass) FRP	BL	BL	12	12	20"	20	White	WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned. PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS ARTICLES: 4.1 LETTER (a) (ii)

4.3

13

Design code: EN 13121-3